

HIGH POWER BROAD BAND LIMITERS

25 WATT CW, 0.5 - 12 GHz

New

- Low limiting threshold (+6 dBm Typical+)
- 25 Watt CW and 200 Watt Peak (1 Microsec) power handling capability
- Built-in DC block @ input and output
- Hermetically sealed module
- Typical Recovery Time is less than 10 microsec



Typical Performance @ +25 Deg. C

MODEL	FREQUENCY RANGE (GHz)	MAXIMUM ¹ INSERTION LOSS (dB)	MAX ¹ VSWR	TYP LIM THRESHOLD (dBm)	MAX LEAKAGE	
					@ 1W CW INPUT (dBm)	@ 25 W CW ² INPUT (dBm)
LS0510 P25A	0.5 - 1.0	0.5	1.4:1	+6	+14	+20
LS0520 P25A	0.5 - 2.0	0.6	1.4:1	+6	+14	+20
LS0540 P25A	0.5 - 4.0	0.7	1.4:1	+6	+14	+20
LS0560 P25A	0.5 - 6.0	1.3	1.5:1	+6	+14	+20
LS05012 P25A	0.5 - 12.0	1.7	1.6:1	+6	+14	+20
LS1020 P25A	1.0 - 2.0	0.6	1.4:1	+6	+14	+20
LS1060 P25A	1.0 - 6.0	1.2	1.5:1	+6	+14	+20
LS1012 P25A	1.0 - 12.0	1.6	1.6:1	+6	+14	+20
LS2040 P25A	2.0 - 4.0	0.7	1.4:1	+6	+14	+20
LS2060 P25A	2.0 - 6.0	1.2	1.5:1	+6	+14	+20
LS2080 P25A	2.0 - 8.0	1.3	1.6:1	+6	+14	+20
LS4080 P25A	4.0 - 8.0	1.3	1.5:1	+6	+13	+18
LS7012 P25A	7.0 - 12.0	1.6	1.6:1	+6	+13	+18

Note 1: Insertion loss and VSWR tested @ -10dBm

Note 2: Power rating derated to 20% @ +125 Deg C.

Herotek

Custom Designs: Please call for Detailed Brochures

Other Herotek Products: Detectors, Amplifiers, Switches, Comb Generators,

Impulse Generators, Multipliers, Integrated Subassemblies

