

PIN DIODE LIMITERS


(Very High Frequency)

1 WATT CW 1 - 40 GHz

New



- Very High frequency Wide Band
- 1 Watt CW Power Handling Capability
- Fast Response & Short Recovery Time (10 nsec typical)
- Hermetically Sealed Module



Typical Performance @ + 25 Deg. C

MODEL	FREQUENCY RANGE (GHz)	MAXIMUM ¹ INSERTION LOSS (dB)	MAX ¹ VSWR	TYP LIM THRESHOLD (dBm)	MAX LEAKAGE ² @ 1W CW INPUT (dBm)
LP1-26A	1 - 26	3.5	2.1	+9	+20
LP2-26A	2 - 26	3.5	2.1	+9	+20
LP18-26A	18 - 26	3.0	2.1	+9	+19
LP18-40A	18 - 40	4.0	2.1	+9	+19
LP1-40A	1 - 40	4.5	2.1	+9	+20
LP2-40A	2 - 40	4.5	2.1	+9	+20
LP26-40A	26 - 40	4.0	2.1	+9	+19

Notes: 1. Insertion loss and VSWR tested @ - 10 dBm.

Notes: 2. Power rating derated to 20% @ +125 Deg. C.

Herotek

Custom Designs: Please call for Detailed Brochures
Other Herotek Products: Detectors,
Amplifiers, Switches, Comb Generators,
Impulse Generators, Multipliers, Integrated Subassemblies



155 Baytech Drive, San Jose, CA 95134 . Tel: (408) 941-8399 . Fax: (408) 941-8388
Email: Info@herotek.com . Website: www.herotek.com . Visa/MasterCard Accepted