

X - BAND HIGH POWER LIMITER

8-12 GHz, 100 Watt CW, 1 KW Peak

New

- High power protection 100W CW and 1 KW peak (1 Microsec pulse width).
- Very low leakage level (+10 dBm typical).
- Low insertion loss and VSWR.
- Ideal for Radar Application.
- Fast recovery time, 1 Microsec typical.
- Built-in DC block @ input and output.
- Hermetically sealed module.



Typical Performance @ + 25 Deg. C (Preliminary)

MODEL	FREQ. RANGE (GHz)	MAXIMUM ¹ INSERTION LOSS (dB)	MAX ¹ VSWR	TYP LIM ² THRESHOLD (dBm)	MAX ³ INPUT CW (Watt)	MAX INPUT ³ PEAK PULSE WIDTH (Watt)	TYPICAL LEAKAGE		
							@ 1 W CW INPUT (dBm)	@ 25 W CW INPUT (dBm)	@ 100 W CW INPUT (dBm)
LS0812PP100A	8 - 12	2.0	2:1	+4	100	1000	+6	+10	+13

Note 1: Insertion loss and VSWR tested @ -10dBm

Note 2: Limiting threshold level @ input power which makes insertion loss 1 dB higher than that @ -10 dBm.

Note 3: Power rating derated to 20% @ +125 Deg C.



Custom Designs: Please call for Detailed Brochures
Other Herotek Products: Detectors, Amplifiers, Switches, Comb Generators, Impulse Generators, Multipliers, Integrated Subassemblies



155 Baytech Drive, San Jose, CA 95134 . Tel: (408) 941-8399 . Fax: (408) 941-8388
Email: Info@herotek.com . Website: www.herotek.com . Visa/MasterCard Accepted