

Timing and Frequency Control


Wi2Wi designs and manufactures a broad range of "PDI Brand" hermetically sealed products to address the unique demands of the avionics, space, medical and military markets. These include frequency control and timing devices; as well as quartz crystals, quartz crystal filters, quartz crystal clock oscillators, TCXOs and OCXOs. . These products are available in both standard and customized platforms, and are manufactured in the Company's MIL-PRF-55310 and QPL qualified manufacturing facility in Middleton, Wisconsin.

Corporate Headquarters

2107 N. 1st Street, Ste. 680 San Jose, CA 95131 Phone: 1.408.416.4200 Fax: 1.608.831.3343 http://wi2wi.com/

Middleton Office

8840 N. Greenview Drive Middleton, WI 53562 Phone: 1.800.274.9825 Phone: 1.608.831.4445 Fax: 1.608.831.3343







Oscillators

Clock Oscillators

- HCMOS, LVDS, LVPECL
- -40°C to 85°C, -55°C to +125°C
- 1.8v, 2.5v, 3.3v 5v supply http://wi2wi.com/clock-oscillators/

QPL Oscillators

- HCMOS, LVCMOS
- -55°C to 125°C, 3.3v and 5v http://wi2wi.com/qpl-oscillators/

OCXO Oscillators

- HCMOS, Sine wave
- ±0.01ppm, -40°C to 85°C
- •3.3v, 5v supply

http://wi2wi.com/ocxo/

TC(V)CXO Oscillators

- HCMOS, LVDS, LVPECL, Sine and Clipped wave
- ±1.0ppm, -40°C to 85°C, -55°C to 105°C
- •3.3v, 5v, 12V, 15V, 24V, 28V supply http://wi2wi.com/tcxo-tcvcxo-vcxo/

Frequency Control Products



Crystal Resonators

Through Hole Crystals

- HC49, HC51, HC6, UM1, TO-5, TO-8
- -40°C to 85°C, -55°C to +125°C
- AT, SC and special cuts available http://wi2wi.com/crystals/

SMD Crystals

- HC49S, 7x5, 5x3.2, 2.5x2.0, 2.0x1.6
- -40°C to 85°C, -55°C to +125°C
- AT, SC and special cuts available http://wi2wi.com/crystals/

S8 SMD Crystals

- 4 point mount extremely rugged package
- Low profile 8.0 x 8.0 x 2.45mm
- AT, SC and special cuts available http://wi2wi.com/crystals/





Crystal Filters

Individual Monolithic packages

- HC49, HC51, UM1, UM5, TO-5, TO-8
- -40°C to 85°C, -55°C to +125°C
- 2, 4, 6, and 8 pole matched sets available http://wi2wi.com/crystal-filters/

SMD Monolithic packages

- 5x7mm low profile compact filter
- -40°C to 85°C, -55°C to +125°C
- 2, 4, 6, and 8 pole matched sets available http://wi2wi.com/crystal-filters/

Finished Filter Assemblies

- Hermetic Drawn cans and covers
- SMD, leaded pin contacts or RF connectors
- Custom packages available upon request http://wi2wi.com/crystal-filters/

Call 1.800.274.9825 or go online for any inquires http://wi2wi.com/